



Non-Slip Safety Tapes

Tape Dimensions

Length of Roll	20 metres
Width of Tape	50/60/70mm
Thickness of Tape	1mm

Non-Slip Tape Features

Tested under Australia's harshest conditions
UV Resistant and performs well under cold conditions
Waterproof polymer base ensuring a strong bond

Range	Guardian Non-Slip Safety Tape
Material	Silicon Carbide 36# Grit
Substrates	Smooth Concrete, Granite, Tiles, Vinyl, Rubber, Timber
Installation	Peel, Bond and Walk® Technology – Adhesive-fixed Design
Standards	Complies with National Construction Code - Building Code of Australia D3.8 Manufactured to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 4586-2013
Warranty	Guaranteed for 2 Years

CSIRO Slip Resistant Testing

AS/NZS 4586-2004	OIL - WET Ramp	Mean overall acceptance angle = 36.4°	Class R13
AS/NZS 4586-2004	WET Pendulum (Four S slider)	Mean BPN = 80	Class V

Guardian Colour and Stock Codes

Colours	Application	50mm Width	60mm Width	70mm Width
Black	Internal and External	TAPE-C-50BK	TAPE-C-60BK	TAPE-C-70BK
Safety Yellow	Internal and External	TAPE-C-50YL	TAPE-C-60YL	TAPE-C-70YL
Medium Grey	Internal and External		TAPE-C-60MG	TAPE-C-70MG

Depth & Luminance Requirements

The National Construction Code of Australia and the AS/NZS 1428.1-2009 require a minimum depth of 50mm.

The National Construction Code of Australia and the AS/NZS 1428.1-2009 require a minimum luminance contrast of 30% with the base surface.