


## Heavy Duty Anodised Aluminium Profiles

Product	Aluminium Corrugated Strip 3x50mm
Material	Anodised Aluminium (Fixing heads will be visible if required)
Size	Cut-to-size up to 5m*
Substrates	Timber, Concrete, Tiles, Vinyl, Thin Carpet (Not suitable for carpet with underlay)
Standards	Manufactured to Australian Standards AS/NZS 1428.1 National Construction Code D2.13 and D2.14
Warranty	Guaranteed for 5 Years



## Slip Resistant Testing

AS/NZS 4586:2013	WET Pendulum Analysis	Slip Resistance Value (SRV) = 45	Class P5
------------------	-----------------------	----------------------------------	----------

## Guardian Colour and Stock Codes

Colours	Application	Corrugated Strip
Silver Anodised	Internal and External	GSN-02COS-SV
Gold Anodised	Internal and External	GSN-02COS-GD
Black Anodised	Internal and External	GSN-02COS-BK

## Luminance Reflective Value

Colours	Mean Dry Luminance (LRV)	Mean Wet Luminance (LRV)
Silver Anodised	40.19	39.43
Gold Anodised	23.21	22.87
Black Anodised	2.22	2.22

## Luminance Contrast Requirements

The National Construction Code of Australia and the AS/NSZ 1428.4.1 require a minimum luminance contrast.

The luminance contrast guideline for Stair Nosings to contrast against the base surface is as follows:

- The strip of contrasting colour shall have a minimum contrast of 30% against the substrate.
- The strip of contrasting colour shall be 50mm–75mm wide.

\*Lengths greater than 2.5m may have an additional cost