



Fiberglass Stair Nosing Profile

Range	Guardian Anti-slip Stairnosing
Material	36# Silicon Oxide Grit
Size	Supplied in 3.62 metre lengths
Substrates	Metal, Concrete, Timber, Tiles, Pavers
Standards	National Construction Code D2.13 / D2.14 Manufactured to Australian Standards AS/NZS 1428.1
Warranty	Guaranteed for 2 Years

Stair Nosing Features	
UV Resistant and tested in Australia's harsh conditions	
Waterproof vinyl ester resin	
Aggressive non-slip surface when wet, oily or dusty	
Excellent chemical and corrosion resistance	
Suitable for both interior and exterior use	
Protects and highlights leading edge of step	

Slip Resistant Testing

AS/NZS 4586:2013	WET Pendulum Analysis	Slip Resistance Value (SRV) = 71	Class P5
------------------	-----------------------	----------------------------------	----------

Guardian Colour and Stock Codes

Colours	Application	Bullnose
Yellow	Internal and External	FBR-017010-YL
Black	Internal and External	FBR-017010-BK

Luminance Contrast Requirements

The National Construction Code of Australia and the AS/NSZ 1428.4.1 require a minimum luminance contrast.

The luminance contrast guideline for Stair Nosings to contrast against the base surface is as follow:

- The contrasting colour strip shall have a minimum contrast of 30% against the substrate.
- The contrasting colour strip shall be a continuous 50mm–75mm wide