



Integrated Warning Stainless Steel

Tactile Dimensions

Tactile Thickness	(Base) 3mm
Gap between Centres	50mm
Square Metre Ratio (600mm x 300mm)	5½ tiles per 1m ²

Dome Dimensions

Top of Dome	25mm
Bottom of Dome	35mm
Height of Dome	5mm

Range	Guardian Integrated Tactile Ground Surface Indicator
Material	High Quality - 316 Marine Grade Stainless Steel with Black TPU Insert
Substrates	Concrete, Granite, Aggregate, Tiles, Vinyl, Rubber, Timber, Carpet Tile
Installation	Applied with 6 screw fixings per tactile plate
Standards	Complies with National Construction Code- Building Code of Australia D3.8 Manufactured to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 4586-2013 Manufactured to comply with Main Roads WA Specification
Warranty	Guaranteed for 2 Years

Slip Resistant Testing

AS/NZS 4586-2013	OIL - WET Ramp Analysis	Class R12
AS/NZS 4586-2013	WET Pendulum Analysis	Class P5

Guardian Colour and Stock Codes

Colours	Application	Warning 300x600mm
Black TPU Insert	Internal and External	GTS600300-316TPUBK

Luminance Contrast Requirements

The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast.

The luminance guidelines for TGSi's to contrast against the base surface is as follows:

- The raised section shall have a minimum contrast of 60% when constructed of two materials/colours